

Producer

SIGMA INK

674 Via de la Valle #100
Solana Beach, CA 92075
Ph. (888) 223-5137

Responsible for distribution

PRINTEX

12113 Kirkham Rd
Poway, CA 92064
(858) 513-2418

Date: December 16, 2013

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Identification of the product:

Trade name:

Type of product:

Use:

Producer/Manufacturer:

Liquid.

MP 103 FAST THINNER

Solvent.

Industrial.

See address above.

**For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident**

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. COMPOSITION / INFORMATION ON INGREDIENTS

This product is considered to be hazardous and contains hazardous components.

Substance name	Value(s)	CAS No / EC No / EC Index	Symbol(s)	R-Phrase(s)\I
Solvent Naphtha L. Aromatic	30 to 40%	64742-95-6		
Cumene:	<= 2 %	98-82-8 / 202-704-5 / 601-024-00	-X Xn N	10-37-51/53-65
Xylene:	< 3 %	1330-20-7 / 215-535-7 / 601-022-00-9	Xn	10-20/21-38
Mesitylene:	< 3 %	108-67-8 / 203-604-4 / 601-025-00-5	Xi N	10-37-51/53
1,2,4-trimethylbenzene:	20 to 30 %	95-63-6 / 202-436-9 / 601-043-00-3	Xn N Xi	10-20-36/37/38
Ethyl-3-ethoxypropionate	15 to 25%	763-69-9 / 212-112-9 / -----		52/53
Dimethyl Glutarate	5 to 10%	1119-40-0		
VOC(w%): 100				

3. HAZARDS IDENTIFICATION

Main hazards

Harmful by inhalation.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Flammable.

4. FIRST AID MEASURES

- Inhalation:

If not breathing, give artificial respiration.

Remove victim to fresh air.

- Skin contact:

Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

- Eye contact:

Seek medical advice.

In case of eye contact, immediately rinse with clean water for 10-15 minutes.

- Ingestion:

If swallowed seek medical advice immediately and show this container or label.

DO NOT INDUCE VOMITING.

Depending on condition of the victim:

Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Extinguishing media:	Dry chemical. Carbon dioxide. Alcohol resistant foam.
- Not to be used:	Water.
Special exposure hazards:	Heavier than air, vapors may travel long distances along ground, ignite and flash back to source. When heated to decomposition, emits dangerous fumes.
Protection against fire:	Wear self-contained breathing apparatus, rubber boots and thick rubber gloves.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Wear suitable protective clothing and gloves.
Environmental precautions:	Prevent entry to sewers and public waters.
After spillage and/or leakage:	Clean up any spills as soon as possible, using a non-flammable, absorbent material to collect it.

7. HANDLING AND STORAGE

General:	Avoid all unnecessary exposure. Store according to PGS 15.
Precautions in handling and storage:	Both local exhaust and good general room ventilation must be provided not only to control exposure but also to prevent formation of flammable mixtures. Take precautionary measures against static discharges. Use only non-sparking tools.
Storage:	Close cover tightly after use. Keep away from food, drink and animal feeding stuffs.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection: In case of insufficient ventilation, wear suitable respiratory equipment.
- Hand protection: Nitrilrubber Gloves.
- Skin protection: Wear suitable protective clothing.
- Eye protection: Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

Occupational Exposure Limits:

Ethyl-3-ethoxypropionate: MAC [ppm]: 50
1,2,4-trimethylbenzene: MAC [mg/m³]: 100 MAC TGG-15 min: 200
1,2,4-trimethylbenzene: MAC [ppm]: 20 MAC TGG-15 min: 40
Xylene: TLV-TWA [mg/m³]: 435
Xylene: MAC [mg/m³]: 210 H
Xylene: MAC [ppm]: 50 H
Mesitylene: TLV-TWA [mg/m³]: 125
Mesitylene: TLV-TWA [ppm]: 25
Mesitylene: MAC [mg/m³]: 100 MAC TGG-15 min: 200
Mesitylene: MAC [ppm]: 20 MAC TGG-15 min: 40
Cumene: TLV-TWA [mg/m³]: 246
Cumene: TLV-TWA [ppm]: 50
Cumene: MAC [mg/m³]: 245
Cumene: MAC [ppm]: 100

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid.
Odor:	Characteristic.

Initial boiling point [°C]:	156
Final boiling point [°C]:	180
Density:	0.9
Flash point [°C]:	44
Auto-ignition temperature [°C]:	420
Explosion limits - lower [%]:	0.7
Explosion limits - upper [%]:	9.4
Log P octanol / water at 20°C:	4

10. STABILITY AND REACTIVITY

Hazardous decomposition products: On exposure to high temperature, may decompose, releasing toxic/flammable vapors.

Materials to avoid: Strong acids.
Strong alkalis.
Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

Rat oral LD50 [mg/kg]: >2000

Rabbit dermal LD50 [mg/kg]: >2000

Rat inhalation LC50 [mg/l/4h]: >5

On ingredients:

Solvent Naphtha L. Aromatic: LD 50 Rat: 5,600 mg/kg

Solvent Naphtha L. Aromatic: LC 50 Rat: (>) 10200 mg/m³; 4h

Solvent Naphtha L. Aromatic: LD 50 Rat: (>) 4000 mg/kg

Ethyl-3-ethoxypropionate: Rat oral LD50 [mg/kg]: 4300

Ethyl-3-ethoxypropionate: Rabbit dermal LD50 [mg/kg]: > 20

Ethyl-3-ethoxypropionate: Rat inhalation LC50 [mg/l/4h]: > 1000

Ethyl-3-ethoxypropionate: Sensitization: No known effects from this product.

Ethyl-3-ethoxypropionate: Acute effects general: Irritation to eyes.

Ethyl-3-ethoxypropionate: Acute effects at high concentrations: Dizziness, drowsiness, confusion, headache, feeling of drunkenness and conscience impairment,

Ethyl-3-ethoxypropionate: Chronic effects: Repeated or prolonged skin contact may cause dermatitis and defatting.

1,2,4-trimethylbenzene: Acute effects general: Nausea, vomiting, abdominal problems, irritation of the respiratory tract, risk of respiration pneumonia, risk of lung edema, irritation of the eye fabric.

1,2,4-trimethylbenzene: Acute effects at high concentrations: Dizziness, giddiness, headache, vomiting, heart rhythm disorder, distress of the central nervous system and consciousness disorder.

1,2,4-trimethylbenzene: Chronic effects: Long term or repeated exposure may cause kidney and liver damage or failure and change of blood composition

Xylene: - Dermal: Absorbed through the skin.

Xylene: Rat oral LD50 [mg/kg]: > 2000

Xylene: Rabbit dermal LD50 [mg/kg]: > 2000

Xylene: Rat inhalation LC50 [mg/l/4h]: > 5

Xylene: Mutagenicity: No effects on laboratory animals.

Xylene: Reproductive toxicity: Possible risk of harm to the unborn child.

Xylene: Acute effects general: Irritation to eyes, skin and respiratory tract.

Xylene: Acute effects at high concentrations: Dizziness, drowsiness, confusion, headache, feeling of drunkenness and conscience impairment,

Xylene: Chronic effects: Long term or repeated exposure can result in: redness, dryness, irritation, rash and inflammation of the skin and damage of kidney and liver.

Xylene: Symptoms on intake of large quantities.: Aspiration of this material may cause chemical pneumonia.

Mesitylene: Acute effects general: Symptoms of exposure to vapors include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision, abdominal pain, irritation of mucous membranes of nose, eyes and abdomen.

Mesitylene: Chronic effects: Long term or repeated exposure can result in: redness, dryness, irritation, rash and inflammation of the skin and damage of kidney and liver.

Cumene: - Dermal: Absorbed through the skin.

Cumene: Acute effects general: Irritation to eyes, skin and respiratory tract.

Cumene: Acute effects at high concentrations: Symptoms of exposure to vapors include drowsiness, weakness, headache, dizziness, nausea, vomiting, dimming of vision, abdominal pain, irritation of mucous membranes of nose, eyes and abdomen.

12. ECOLOGICAL INFORMATION

ABM(The Netherlands): {8} Harmful to aquatic organisms.
Contains substances dangerous to the aquatic environment.

Cleansing effort A

Biodegradation [%]: 78

LC50-96 Hour - fish [mg/l]: 18

48 Hour-EC50 - Daphnia magna [mg/l]: 21

IC50 72h Algae [mg/l]: No data available.

COD(gO2/g): 2.6g O2/g

BOD 5 (gO2/g): 1.2

WGK class (Germany): 1

On ingredients:

Ethyl-3-ethoxypropionate: Surface water polluting: Weakly.

Ethyl-3-ethoxypropionate: Risk of drinking water pollution (ground water): Yes.

Ethyl-3-ethoxypropionate: LC50-96 Hour - fish [mg/l]: 65

Ethyl-3-ethoxypropionate: 48 H-LC50 - Daphnia magna [mg/l]: > 480

Ethyl-3-ethoxypropionate: IC50 72h Algae [mg/l]: > 115

Ethyl-3-ethoxypropionate: WGK class (Germany): 1

1,2,4-trimethylbenzene: Danger of accumulation in the food chain.

1,2,4-trimethylbenzene: Toxic to aquatic organisms.

Xylene: Log P octanol / water at 20°C: 3.1

Xylene: LC50-96 Hour - fish [mg/l]: > 1

Xylene: 48 H-LC50 - Daphnia magna [mg/l]: > 1

Xylene: IC50 72h Algae [mg/l]: > 10

Xylene: Toxic to aquatic life.

Xylene: WGK class (Germany): 2

Mesitylene: Toxic to aquatic organisms.

Mesitylene: Danger of accumulation in the food chain.

Cumene: Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Disposal: Dispose in a safe manner in accordance with local/national regulations.

Industrial waste number: Eural:200127.

14. TRANSPORT INFORMATION

Hazard Label(s): UN 1993 Flammable Liquid, N.O.S. (Aromatic Petroleum Naphtha)

Shipping name: 1993

- UN No.: 30

- H.I. nr.: Class: 3

- ADR/RID: III

Group: Packaging group: III

- IMO-IMDG: Class 3

- ICAO/IATA: 1993

15. REGULATORY INFORMATION

Symbol(s): Harmful.

R Phrase(s): R10: Flammable.
R20: Harmful by inhalation.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S Phrase(s): S3: Keep in a cool place.

MSDS-MP 103 FAST THINNER

S16: Keep away from sources of ignition - No smoking.
S35: This material and its container must be disposed of in a safe way.
S51: Use only in well-ventilated areas.
S57: Use appropriate container to avoid environmental contamination.
S59: Refer to manufacturer/supplier for information on recovery/recycling.
S61: Avoid release to the environment. Refer to special instructions/Safety data sheets.
P201-For professional use only.

P Phrase(s):

16. OTHER INFORMATION

Text of R-Phrases in § 2:

R10: Flammable.
R11: Highly flammable.
R20: Harmful by inhalation.
R20/21: Harmful by inhalation and in contact with skin.
R36/37/38: Irritating to eyes, respiratory system and skin.
R37: Irritating to respiratory system.
R38: Irritating to skin.
R45: May cause cancer.
R48/23/24/25: Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.

The contents and format of this SDS are in accordance with EEC Commission Directive 2001/58/EC.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document