



Material Safety Data Sheet

MP-201 Glass Hardener

Date: April 7, 2012

Producer

SIGMA INK

674 Via de la Valle #100
Solana Beach, CA 92075
Ph. (888) 223-5137

Responsible for distribution

PRINTEX

Date: December 4, 2012

12113 Kirkham Rd
Poway, CA 92064
(858) 513-2418

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY /UNDERTAKING

Trade name: MP 201 GLASS HARDENER

Type of product:

Use:

Producer/Manufacturer:

Curing agent

Industrial.

See address above.



**For Hazardous Materials [or Dangerous Goods] Incident
Spill, Leak, Fire, Exposure, or Accident**

Call CHEMTREC Day or Night

Within USA and Canada: 1-800-424-9300

Outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. COMPOSITION / INFORMATION ON INGREDIENTS

This product is considered to be hazardous and contains hazardous components.

Substance name	Value(s)	CAS No / EC No /	Symbol(s)	R-Phrase(s)
2-methoxy-1-methylethyl acetate:	20 to 30 %	108-65-6 / 203-603-9	Xi	10-36
Aliphatic poly isocyanate:	70 to 80 %	28182-81-2 / -----	Xi	42/43
Hexamethylene-di-isocyanate:	< 0.5 %	822-06-0 / 212-485-8	T	23-36/37/38-42/43
ADHERING ADDITIVE	4 TO 10%	82985-35-1		
VOC(w%): 25				

3. HAZARDS IDENTIFICATION

Main hazards: Flammable.
Irritating to eyes.
May cause sensitization by skin contact.

4. FIRST AID MEASURES

- Inhalation: If not breathing, give artificial respiration.
Remove victim to fresh air.

- Skin contact: Remove affected clothing and wash all exposed skin area with mild soap and water,
followed by warm water rinse.

- Eye contact: Seek medical advice.
In case of eye contact, immediately rinse with clean water for 10-15 minutes.

- Ingestion: If swallowed seek medical advice immediately and show this container or label.
DO NOT INDUCE VOMITING.

Depending on condition of the victim: Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Dry chemical.
Carbon dioxide.
Alcohol resistant foam.

- Not to be used: Water.

MP-201 Glass Hardener

Special exposure hazards:

Heavier than air, vapors may travel long distances along ground, ignite and flash back to source. When heated to decomposition, emits dangerous fumes.

Protection against fire:

Wear self-contained breathing apparatus, rubber boots and thick rubber gloves.

6. ACCIDENTAL RELEASE MEASURES

General precautions:

Eliminate every possible source of ignition.

Personal precautions:

Wear suitable protective clothing and gloves.

Environmental precautions:

Prevent entry to sewers and public waters.

After spillage and/or leakage:

Dike for recovery or absorb with appropriate (non-flammable) material.

7. HANDLING AND STORAGE

General:

Avoid all unnecessary exposure.

Store according to PGS 15.

Precautions in handling and storage:

Both local exhaust and good general room ventilation must be provided not only to control exposure but also to prevent formation of flammable mixtures.

Take precautionary measures against static discharges.

Use only non-sparking tools.

Storage:

Close cover tightly after use.

Keep away from food, drink and animal feeding stuffs.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

- Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment.

- Hand protection:

Nitrilrubber Gloves.

- Skin protection:

Wear suitable protective clothing.

- Eye protection:

Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.

Occupational Exposure Limits:2-methoxy-1-methylethyl acetate: TLV-TWA [mg/m³]: 274 (8 h.)

2-methoxy-1-methylethyl acetate: TLV-TWA [ppm]: 50 (8 h.)

2-methoxy-1-methylethyl acetate: TLV-STEL [mg/m³]: 548 (15 min.)

2-methoxy-1-methylethyl acetate: TLV-STEL [ppm]: 100 (15 min.)

2-methoxy-1-methylethyl acetate: MAC [mg/m³]: 550

2-methoxy-1-methylethyl acetate: MAC [ppm]: 100

Hexamethylene-di-isocyanate: MAC [mg/m³]: 0.04

Hexamethylene-di-isocyanate: MAC [ppm]: 0.005

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:

Viscous liquid.

Colour:

Clear.

Odour:

Characteristic.

Initial boiling point [°C]:

150

Density:

1.07

Viscosity:

>60S 6mm ISO-cup

Flash point [°C]:

54

Auto-ignition temperature [°C]:

425

Explosion limits - lower [%]:

1.5

Explosion limits - upper [%]:

10.8

10. STABILITY AND REACTIVITY

Hazardous decomposition products:

On exposure to high temperature, may decompose, releasing toxic/flammable vapors.

Materials to avoid:

Strong oxidizers.

Strong alkalis.

Strong acids.

Conditions to avoid:

Extremely high or low temperatures.

Moisture.

11. TOXICOLOGICAL INFORMATION

Rat oral LD50 [mg/kg]: >5000

Rabbit dermal LD50 [mg/kg]: >2000

Rat inhalation LC50 [mg/l/4h]: >20

On ingredients:

2-methoxy-1-methylethyl acetate: Rat oral LD50 [mg/kg]: 8532

2-methoxy-1-methylethyl acetate: Rabbit dermal LD50 [mg/kg]: > 5000

2-methoxy-1-methylethyl acetate: Mutagenicity: No effects on laboratory animals.

2-methoxy-1-methylethyl acetate: Acute effects general: Irritating to eyes.

2-methoxy-1-methylethyl acetate: Acute effects at high concentrations: This material or its emissions may cause damage to kidney and liver and/or aggravate existing disorders.

2-methoxy-1-methylethyl acetate: Chronic effects: Longterm or repeated exposure can result in: redness, dryness, irritation, rash and inflammation of the skin and damage of kidney and liver.

Hexamethylene-di-isocyanate: Sensitization: May cause sensitization by inhalation and skin contact.

Hexamethylene-di-isocyanate: Acute effects general: Irritating to eyes and respiratory system.

Hexamethylene-di-isocyanate: Acute effects at high concentrations: Dizziness, drowsiness, confusion, headache, feeling of drunkenness and conscience impairment,

Hexamethylene-di-isocyanate: Chronic effects: Long exposure to low concentrations may lead to dermatitis, bronchitis and conjunctivitis.

12. ECOLOGICAL INFORMATION

ABM(The Netherlands): {9} Harmful to aquatic organisms.

Cleasing effort B

LC50-96 Hour - fish [mg/l]: >100

48 Hour-EC50 - Daphnia magna [mg/l]: >100

IC50 72h Algae [mg/l]: >100

COD-value [mg/l]: No data available.

BOD5-value [mg/l]: No data available.

WGK class (Germany): 1

On ingredients:

2-methoxy-1-methylethyl acetate: Log P octanol / water at 20°C: .43

2-methoxy-1-methylethyl acetate: Surface water poluting.: Weakly.

2-methoxy-1-methylethyl acetate: Aquatic organisms.: Little harmful to fish and aquatic organisms.

2-methoxy-1-methylethyl acetate: Biodegradation [%]: 83

2-methoxy-1-methylethyl acetate: 96 Hour-LC50 - Minnow [mg/l]: 161

2-methoxy-1-methylethyl acetate: 48 H-CE50 - Daphnia magna [mg/l]: 408

2-methoxy-1-methylethyl acetate: Bioaccumulative potential: Not expected.

2-methoxy-1-methylethyl acetate: WGK class (Germany): 1

13. DISPOSAL CONSIDERATIONS

Disposal: Dispose in a safe manner in accordance with local/national regulations.

Industrial waste number: Eural:200127.

14. TRANSPORT INFORMATION**Hazard Label(s)**

Shipping name: UN 1263 Paint Related Material , 3, III

- H.I. nr.: 30

- ADR/RID: Class: 3

Transport in accordance with 2.2.3.1.5 ADR (not regulated for containers <450l.)

Group: III

- IMO-IMDG: Packaging group: III

Class 3

Transport in accordance with 2.3.2.5 IMDG (not regulated for containers <30 l.)

15. REGULATORY INFORMATION

Symbol(s): Harmful.

R Phrase(s): R10: Flammable.

R36: Irritating to eyes.

MP-201 Glass Hardener

S Phrase(s):

R42/43: May cause sensitization by inhalation and skin contact.

S3: Keep in a cool place.

S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe the gas, fumes, vapors, spray.

S24: Avoid contact with skin.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S35: This material and its container must be disposed of in a safe way.

S36/37: Wear suitable protective clothing and gloves.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible).

S51: Use only in well-ventilated areas.

S59: Refer to manufacturer/supplier for information on recovery/recycling.

P Phrase(s):

P91-Contains isocyanates. See information supplied by the manufacturer.

P99: Contains: - Aliphatic poly isocyanate - Hexamethylene-di-isocyanate. May produce an allergic reaction.

Labelling:

Contains: Isocyanates.

Safety advises:

This product contains isocyanates and can be irritating on the mucous membrane and the respiratory organs and cause an over-sensitive reaction. Inhaling vapors or spray may cause sensitization. Processing this product, all precaution measures must be observed. Persons who suffer from an allergy, asthma or chronic disorder of the respiratory system, should not be involved in working with this product.

16. OTHER INFORMATION

Text of R-Phrases in § 2:

R10: Flammable.

R23: Toxic by inhalation.

R36: Irritating to eyes.

R36/37/38: Irritating to eyes, respiratory system and skin.

R42/43: May cause sensitization by inhalation and skin contact.

The contents and format of this SDS are in accordance with EEC Commission Directive 2001/58/EC.

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This MSDS was prepared and is to be used only for this product. If the product is used as a component in another product, this MSDS information may not be applicable.

End of document